


ecore[™]
INTERNATIONAL

E-Grip[™] III

flooring adhesive



E-Grip III is a revolutionary zero-VOC adhesive. The low odor, one-component urethane adhesive is formulated specifically for use with E-CORE's family of surfacing products. It features excellent trowability and improved tack properties, making it easy to apply and create flat, concealed seams. E-Grip III has been specifically engineered to be solvent-free. With a moisture-cured, no-mix, non-sag and permanently elastic formula, it provides excellent adhesion to elastomers, concrete, and wood in both indoor and outdoor applications.

ADVANTAGES

- Zero-VOC formula (SCAQMD Rule #1168)¹
- Easy to trowel and apply
- Solvent Free
- No mixing required
- Excellent curing cycle
- Very low odor
- Non-flammable
- Available in 2 gallon and 4 gallon pails, and 10.1 oz cartridges
- Meets Collaborative for High Performance Schools (CHPS) Low-Emitting Materials criteria (CA Section 01350)²
- Can contribute towards obtaining LEED credits

¹ SCAQMD is the California "South Coast Air Quality Management District" Rule 1168 for adhesive flooring and sealant applications. The VOC content in E-Grip III complies with all adhesive applications listed by the SCAQMD.

² E-Grip III flooring adhesive meets the testing and product requirements of the California Department of Public Health (CDPH) Standard Method v. 1.1-2010 (Emissions Testing Method for CA Specification 01350).

Flooring Adhesive

PHYSICAL DATA

Adhesive Type:	Single component polyurethane		
Color:	Gray	Maximum RH:	85% per ASTM
Antimicrobial:	Yes		F-2170
Adhesive Cure System:	Moisture-cured	Freeze/Thaw Stability:	Stable
VOC Content:	0 lbs/ gal (calculated)	Application Temp:	40°F to 100°F
Solvents:	0 lbs/ gal (calculated)	Flashpoint:	> 500°F
Moisture Vapor:	Maximum 5.5 lbs per	Shelf Life:	12 Months
Emission of Concrete Floor:	ASTMF 1869	Working Time:	30-40 mins

TROWEL SIZE

APPROX. COVERAGE

1/16" x 1/32" x 5/64" U-notch*	120 sq ft/ gal
1/16" x 1/16" x 1/16" square notch	95 sq ft/ gal
1/8" x 1/8" x 1/8" square notch	60 sq ft/ gal

*Recommended trowel size for 3.2mm material

TECHNICAL DATA

For technical data, please call 1.800.322.1923

HEALTH & HAZARD RATINGS

	NFPA	HMIS
Health	1	1
Fire	0	0
Reactivity	0	0
Protective Equipment	None	C

For handling and precautionary information, reference the product label and material safety data sheet.



ECORE International
715 Fountain Avenue • Lancaster, PA 17601
www.ecoreintl.com

All data statements and information presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification.

Copyright© 2013 Ecore International