# **Product** Options

Roll goods and interlocking tiles are available standard in an 8 millimeter thickness. Custom thicknesses and tiles options are also available.

8mm x 48" (1.2m) 6mm x 48" (1.2m) \* 9mm x 48" (1.2m) \*



8mm x 23" (58cm) x 23" (58cm)\* 8mm x 24" (61cm) x 24" (61cm)\*

8mm x 36" (91cm) x 36" (91cm)\*

\*For all custom options, please contact your local representative to determine availability, pricing, minimums, and lead times.

# Physical Data

PERFORMANCE CRITERIA		RESULT
Tensile Strength	ASTM D412	200 lb/in² min.
_Flexibility	ASTM F137	Pass 1/4-inch mandrel
Static Load (1000 lb/in²)	ASTM F970	Less than 0.020-inches
Coefficient of Friction	ASTM 2047	Greater than 0.9-inches
	ASTM C518	0.406 BTU-in/hr-ft <sup>2</sup> -°F
Ambient Noise Reduction	ASTM C423	0.10 Sabin/ft²
Impact Insulation Class	ASTM E492	45 Minimum
Sound Transmission Coefficient	ASTM 413	45 Minimum
Ball Rebound	EN 12235	Pass
FloorScore	CA Specification 01350	<u>Certified</u>

Pass
Certified

## Can a floor be the original, timeless, and recycled all at the same time?





### **Everlast Basic Rolls and Tiles**

are the "original" recycled rubber fitness floor. Available in rolls and tiles, this durable surface sets the standard for performance, quality, and affordability.





### What does it take to be a floor?


Durable
Sustainable
Affordable
Ease of Maintenance
Slip Resistant

This basic fitness floor is the product of Ecore's vertically integrated manufacturing capability. Turning the durability and performance of a tire into a floor, Ecore takes pride in transforming waste into an industry.



Ecore Athletic products provide good ergonomics, safety and acoustic benefits.





### Applications



Ť



Light Weights

Ice Rinks Strength

Strength Equipment