

# Surfacing for Off-Ice Areas



## Anti-Slip and Blade-Resistant

Using only the finest quality recycled rubber and state-of-the-art technology, Ecore International manufactures rubber flooring for the most demanding situations at low cost. Everlast rolls are durable enough to withstand constant abuse and high traffic while providing comfort and safety.

## Areas of Application:

- Locker rooms
- Pro shops
- Rink perimeters
- Walkways
- Game rooms
- Snack bars

## Product Attributes

- Extremely durable
- Blade resistant
- Slip resistant even when wet
- Sound and shock absorbent
- Seamless appearance
- Custom graphic inlays
- Easy installation
- Made from recycled rubber
- Made in the U.S.A

ecore™

Athletic

## Maintenance

Most installations require only one routine vacuuming and wet mopping with clean water and mild detergent or pH neutral solutions.

## Installation


Everlast rolls installed in ice arena applications require a permanent full-spread adhesive system. For more detailed installation recommendations, please request an Everlast Installation and Maintenance Manual by calling: 866-795-2732 or visiting [www.ecoreathletic.com](http://www.ecoreathletic.com)

## Warranty


All flooring is guaranteed by Ecore to be free from manufacturing defects on both material and workmanship. If such a defect is discovered within three years under normal non-abusive conditions, the sole remedy against the seller will be the replacement or repair of the defective goods, or at the seller's option, credit may be issued not exceeding the selling price of the defective goods.




EL00 Basic Black



EL01 Buff Blue 10



EL02 Grippin' Gray 10



EL05 Rippin' Red 10

More colors available with a minimal purchase. For more information call 866.795.2732.

## Product Dimensions

Everlast Rolls  
48" width

Thickness  
9mm (3/8")

Weight (lbs/sq ft)  
1.95

## Physical Data Test

|                             | ASTM            | Everlast SBR Rubber                 |
|-----------------------------|-----------------|-------------------------------------|
| Tensile Strength            | D412            | 200lb/in <sup>2</sup> min           |
| Flexibility                 | F137            | Pass 1/4 inch madrel                |
| Coefficient of Friction     | D2407           | →0.9                                |
| Thermal Conductivity        | C518            | 0.406 Btu-in/hr-ft <sup>2</sup> -F° |
| Static Load Limit           | F970, 1,000lbs. | ←0.020 in                           |
| Chemical Resistance         | F925            | no charge                           |
| Impact Insulation Class     | E492            | 45 min                              |
| Noise Reduction Coefficient | C423            | 0.10 sabine/ft <sup>2</sup>         |
| Elongation at Break         | D412            | 75% min                             |